

Product Specifications

Heavy Duty Range

170KGIKG – High Back

- 1) Mechanism
 - ▯▯ Knee Tilt mechanism with back tension adjustment, 5 position lock
 - ▯▯ Right hand controls
 - Height adjustment lever
 - ▯▯ Left hand controls
 - Turn lever upwards for constant back contact – free floating
 - Turn lever downwards to lock back in position
- 2) Gas Spindle
 - ▯▯ Executive double taper – Class 3
- 3) Base
 - ▯▯ 700mm Cast Aluminium base with 50mm 4 x 4 hooded castors
- 4) Single laminated plywood shell
 - ▯▯ Reinforced pressed plywood – 20 to 25mm thick
 - ▯▯ Seat
 - Laminated VC64 chip foam and VP70 high density foam
 - ▯▯ Back
 - VP30 medium density foam
- 5) Arm options
 - ▯▯ Black powder coated steel “C” arm with PU arm pad
 - ▯▯ Chrome “C” arm with PU arm pad



| Dimensions | | 170KGIKG |
|----------------|---------|----------|
| Overall Height | | 1260 mm |
| Overall Width | | 680 mm |
| Overall Depth | | 700 mm |
| Total Weight | | 23 kg |
| Seat Height | Lowest | 510 mm |
| | Highest | 600 mm |

